



Model No's. **RPC-20-HW** Stand-alone unit, hardwired

Lowell's Remote Power Control can be utilized with a variety of switches and control systems or devices that provide either a dry contact closure or voltage output (5V-24V, AC or DC, 3mA) to provide an intrinsically safe low voltage method of controlling AC power to equipment at a remote location. The ability to safely control AC power distribution without directly accessing equipment minimizes the potential for unauthorized activation. Typical applications include commercial, entertainment, government, education and house-of-worship venues where remote power control is often required.

Installation

RPCs are typically installed in close proximity to equipment to be controlled. Low-voltage cable is run from the RPC terminal strip to a control switch (such as a switch from Lowell's RPS Series) or other control method. Systems can be configured with multiple RPCs activated by a single switch or trigger voltage source. Systems can also be configured with multiple switches or trigger voltage sources controlling a single RPC. (See connection diagrams on next page.) RPCs also serve as a key component in Lowell's low voltage sequential control systems (SEQ Series).



Construction & Features

- · Compact steel chassis with black powder epoxy finish
- Power Rating: 20A 125VAC
- One duplex outlet
- Terminates with 6-ft. non-metallic flexible 1/2" conduit (field-trimmable)
- ETL Listed (UL 60065) in U.S.A. and Canada
- Made in the U.S.A.

A&E Specifications

The device for remotely controlling AC power shall be Lowell Remote Power Control Model No. RPC-20-HW, which shall include a power supply and relay housed in a 7.5"L x 3.25"W x 2.75" steel chassis with a black powder epoxy finish. The unit shall include one duplex outlet with 20A power rating and six-ft. non-metallic flexible conduit termination.

Related Accessories (order separately)

- RPS Series: Selection of rackmount and wall-mount SPST maintained and momentary switches with rocker or key activation.
- SEQ Series: Selection of modular low voltage sequencers.
- MSM2: Momentary Switch Module used with momentary contact switches

Model Numbers

Model No.	Description	Chassis Length	Chassis Width	Chassis Height	Total Outlets	Switch Type
RPC-20-HW	Low voltage remote power control	7.5"	3.25"	2.75"	2 (20A 125VAC)	(see page 2)

Lowell makes every effort to provide accurate information while reserving the right to change specifications and/or improve manufacturing methods without notification. ©2016 Lowell Manufacturing Company, 100 Integram Dr., Pacific MO 63069 | 800.325.9660 | www.lowellmfg.com





ON = power applied to receptacles (i.e. receptacles active)

 $\mathsf{OFF} = \mathsf{no} \ \mathsf{power} \ \mathsf{to} \ \mathsf{receptacles}$

EXAMPLE 1

Typical RPC Control Methods: low voltage, limited current Class 2 wiring





EXAMPLE 2



Dry Contact Closureor open-collector transistor switch provided by external sequencer (Lowell SEQ Series) or control system (by others). Follow polarity indicators, if any, on sequencer/controller. (min. rating: 30V, 40mA)

ON = connection applied (closed) OFF = connection removed (open)



EXAMPLE 3

Voltage output from external control system (by others). (5-24 volts, AC or DC, 3mA max)

ON = voltage applied OFF = voltage removed

FIRE ALARM PANEL INTERFACE

APPLICATION EXAMPLE: RPC controls the power to a retail store music/paging system. The Fire Alarm Panel contact closure forces the music/ paging system OFF so the alarm can be heard.

NOTE: A normally closed (NC) contact from Fire Alarm Panel can be used as shown in Example 2 (at left).



Voltage from +24V Out through resistor to Trigger Input holds power to receptacle "ON." Shunting Trigger Input to Com via Fire Alarm Panel contact closure forces power to receptacle "OFF."

* Not included

LED

Lowell makes every effort to provide accurate information while reserving the right to change specifications and/or improve manufacturing methods without notification. ©2016 Lowell Manufacturing Company, 100 Integram Dr., Pacific MO 63069 | 800.325.9660 | www.lowellmfg.com