

Model No.

XCP84 Steel Backbox

• For 8" speaker

Backbox with flat grille mounting flange is made for recessed installations and will accept an 8" driver and torsion or screw-mount grille. It's ideal for suspended tile ceilings.

Features

- Welded, unitized heavy gauge steel undercoated to eliminate acoustic/metallic resonance includes foam pad in bottom.
- Welded receptacles mount a variety of torsion grilles for a hardware-free look and 8-32 U-clips accept a variety of screw-mount grilles.
- Four combination 0.5"–0.75" conduit knockouts and four 0.5" wire knockouts.
- Black powder epoxy finish
- Made in the U.S.A. with certified U.S. steel.

A&E Specifications

The recessed backbox shall be Lowell Model No. XCP84, which shall be 22-gauge steel undercoated to eliminate acoustic and mechanical resonance. The backbox shall have a 10.06" diameter and 4.06" depth. It shall have four 0.5" to 0.75" knockouts for conduit and four 0.5" knockouts for wire. The backbox shall include a foam pad. It shall be finished in black powder epoxy paint.



Compatible Components (order separately)

- GrillesA8AW, CS8H, CN8M, LO8P, WB8, RS8AW, WB8H, WB8T*
- Channel RailsSS24, SS30
- T-bridgesLBS8, LBS8-R1

NOTE: T-bridge or channel rails are recommended in suspended tile ceilings to transfer speaker assembly weight to ceiling grid.

NOTE: Lowell driver model 8A50 should not be used with this backbox (Use 10"D backbox Model No. XCP810 instead).

Model Number

Product No.	Description	Depth	Diameter	Volume (cu.ft.)	Lining
XCP84	Steel backbox for recessed installations	4.06"	10.06"	0.187	foam pad

* Torsion grilles accept maximum driver/xfmr weight of 3.5 lbs. (typically a driver with 10oz. magnet). Model 8A50 is too heavy to be supported by a torsion grille.

Drawings

