

Model No. LT2-810-72-BB 2x2 Speaker System for Tile Ceilings

- Includes 8" driver, 2x2 grille/subplate, backbox
- Optional volume control

Quick install speaker system for suspended tile ceilings features an 8" dual cone driver, 2'x2' fine perforation grille with subplate and backbox. Ideal for commercial paging and background music.

Features

- Driver (810): 8" 15W dual cone driver with 10 oz. magnet, frequency response of 54Hz-11.6kHz (± 6 dB), 50Hz-20kHz (± 6.6 dB) and sensitivity of 97.9dB avg. measured 1W/1M.
- Transformer (TLM-572): Dual voltage transformer (70/25V) shall feature primary taps at 0.25, 0.5, 1, 2 and 5W.
- Grille with subplate (2'x2'): Fine-perforation grille is designed to provide maximum free-air space for excellent sound transmission while maintaining an unobtrusive appearance in new or existing tile ceilings. Quick install. White finish.
- Backbox (8XD4): 0.147 cu.ft. steel backbox protects driver. Speaker leads exit through a metal clamp for fast connection—just splice connecting wires, push them inside the enclosure and tighten the clamp. Black finish.

A&E Specifications

The speaker system for suspended tile ceilings shall be Lowell Model No. LT2-810-72-BB. The 2'x2' system shall directly replace a 2'x2' ceiling tile. Each speaker system shall include a factory-mounted driver mounted to a subplate with a fine perforation steel grille finished in white powder epoxy. The driver shall be 8" dual cone with a power rating of 15W. It shall have a magnet weight of 10 ozs., frequency response of 54Hz-11.6kHz (± 6 dB); 50Hz-20kHz (± 6.6 dB) and sensitivity of 97.9dB avg. measured 1W/1M. The system shall include a steel backbox (.147 cu.ft.) with leads exiting through a metal clamp. The dual voltage transformer (70/25V) shall feature primary taps at 0.25, 0.5, 1, 2 and 5W.



Assembly is fabricated with four restraint tabs for code compliance. Use the tip of a screwdriver to bend the tab out for tie-offs.



Mounted driver with transformer



Optional volume control knob is hand or screwdriver adjustable. Order Model No. LT2-810-72-BB-VC.



Fine perforation grille

Ordering Option

Model No. LT-810-72-BB-VC: Includes white volume control knob on the grille which can be adjusted by hand or with a screwdriver.

Driver Specifications (half space)

Driver No.	Size	Power Rating	Type	Ceramic Magnet	Frequency Response	Dispersion @2000Hz -6dB	Voice Coil Impedance	Voice Coil Diameter	Sensitivity 1W / 1M	Max SPL**	Depth	Weight
810	8"	15W	Dual cone	10 oz.	54Hz-11.6kHz (± 6 dB) 50Hz-20kHz (± 6.6 dB)	95 degrees conical	8 ohms	1"	97.9dB Avg	109.7dB	2.84"	2.0 lbs.

** Calculated value 1M @ driver power rating.

Additional technical information is available on the spec sheet for driver No. 810

Drawings

