

Model No.

LCDR-3524

• 35U x 24"D x 22.31"W

The configured design rack is an elegant, all-in-one enclosed rack made to fit the high-end decor of executive boardrooms and home theatres. This ready-to-use rack ships already assembled and includes casters for portability plus leg levelers for stability, seven shelves, seven blank panels, two fans, a rear access cover, lockable side panels, and a glass front door.

Construction & Features

- Welded Frame: 16-gauge steel with 16-gauge top and bottom, reinforced at loadbearing junctions
- Overall Height: 68.18" with casters (65.43" rack only)
- Top: Steel top features a center hole with grommet for cable access and 2 vents.
- Fans: 2 whisper fans are installed in the top vents.
- Base: Features an open center, 2 holes with grommets for rear cable access, grounding stud, 4 casters (2 locking), and 4 leg levelers.
- Front Door: Smoked grey tempered glass door with key lock and inset handle can be adjusted to left or right hand swing.
- Rear Access Cover: Opens from top, includes key lock.
- Side Panels: Lift off for easy access. Includes key lock.
- Mounting Rails: 2 pr. adjustable rails with mounting holes tapped 10-32 and rack unit increments printed on EIA spacing.
- Shelves: 7 (2U) steel shelves with bottom vents can be repositioned as needed.
- Panels: 7 (2U) blank panels can be repositioned.
- Load Capacity: 980 lbs.
- EIA/TIA/RoHS: Compliant
- Hardware: PilotPoint™ screws with captive washers
- Finish: Charcoal grey textured finish
- Origin: Made with 100% certified U.S. steel

A&E Specifications

The EIA/TIA compliant 19" equipment rack shall be Lowell Model No. Lcdr-3524 which shall measure 22.31"W x 24.00"D x 68.18"H (with casters). The rack shall have 35U panel space and 980 lbs. load capacity. Construction



shall be fully welded 16-gauge steel with 16-ga. top/bottom reinforced at loadbearing junctions and finished with a charcoal grey textured coating. It shall include a smoked grey tempered glass front door with key lock, recessed rear access cover with key lock, removable side panels with locks, two pairs of 11-gauge steel rails with mounting holes tapped 10-32 and rack unit increments printed on EIA spacing, steel top with 2 vents and a hole with grommet for cable access, seven (2U) shelves with vents, and seven (2U) blank panels. The base shall feature a center opening, 2 holes with grommets for rear cable access, a grounding stud, 4 casters (2 locking) and 4 leg levelers.

Drawings

