



## 224

18/2 Speaker Cable CMR  
Audio, Control, and Low Voltage Power

### Construction & Dimensions

CONSTRUCTION & DIMENSIONS	
CONDUCTOR PARAMETER	
• Number of Conductors	2
• AWG Size	18
• Conductor Stranding	7x26
• Conductor Type	Bare copper
• Nominal DCR	6.2 Ohm/1000ft
• Cabling Lay Length	3.5 in
• Twists/Foot	3.4 twist/ft
INSULATION PARAMETER	
• Insulation Type	Polypropylene - PP
• Insulation Thickness	0.008 in
• Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETER	
• Shield Type	None
ELECTRICAL CHARACTERISTICS	

### Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	PVC
Jacket Thickness	0.017 in
Nominal Cable O.D.	0.156 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Pull Tension	42 lbs
Bend Radius	1.404 in
Cable Weight	19 lbs

### Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



**224**

18/2 Speaker Cable CMR

**Related Products**

RELATED PRODUCTS	
Plenum Number	25224B
Aquaseal Number	AQC224
Aquaseal Direct Burial Number	AQ224
SpeakOn Panel Mount	CN-NL4MP