



12407 Mukilteo Speedway, Ste. 130, Lynnwood, WA 98087
Phone: (425) 322-3170 Fax: (877) 721-6107
info@amkspeakers.com www.amkspeakers.com

AMK Commercial Series

DS82-A

Network powered speakers
Dante™ Enabled Network Audio
8" Coaxial Loudspeaker Assembly
(Preliminary)



Features:

- ♦ Network enabled Loudspeaker by Dante™
- ♦ PoE+ powered without a need for local power.
- ♦ RJ45 connection for audio from PoE+ Ethernet.
- ♦ 8" polypropylene cone with inverted rubber surround.
- ♦ 1" Polyamide dome tweeter
- ♦ Weather and water resistant.
- ♦ Single Channel Audio
- ♦ UL 2043 Listed

The AMK DS82-A is a Dante™ audio network addressable and self-amplified ceiling speaker system. The speaker is powered by PoE+ network switch meaning no external power supply is required. The speaker includes a Class D amplifier which provides effective use of power. This system will solve the issue of having to provide a separate amplifier or I/O interface for speaker installations. The system comes with 8" coaxial 40W loudspeaker driver, CX802, that has excellent dispersion, wide bandwidth and a smooth frequency response makes this the top choice for today's overhead commercial applications.


One PoE+ amplified speaker can power a total of (2) speakers, one active and one passive speaker. This assembly can be used in wide range of projects for paging and background music applications. The DS82-A is ideal for hotels, education, hospitals, retail stores, performing art centers, restaurants, airports, houses of worship, and board rooms.

For details on Dante Networking, please visit:
<https://www.audinate.com/resources/networks-switches>

System Specification		AMK Dante Ceiling Speaker Advantage
Frequency Response	100 Hz - 20 kHz (+/- 3dB)	<ul style="list-style-type: none">* No need to have separate dante enabled amp or I/O interface* A Single RJ45 connection to main active speaker with two conductor wire connection to each of the passive speakers.* Highly efficient speaker driver due to barium ferrite magnet.* Cost effective simple one system solution.
Maximum SPL at 1M	105 dB	
Voice-coil diameter	1."	
Magnet	Barium Ferrite (for high efficiency of the speaker driver)	
Nominal Coverage Angle (500Hz – 4kHz Average)	110° Conical Average	
Audio Input	Dante Audio via Ethernet	
Output Power	10W / Channel (5W per speaker)	
Signal to Noise Ratio	>99dB	
Power consumption	2 Watts Standby, 25 Watts Maximum	
Input connector on active speaker	RJ-45	
Maximum wire length to companion speakers	100ft at 18AWG	
PoE+	IEEE 802.3at-2009	
Controls	Dante™ controller software	
UL Listing	UL 2043	

Physical Speaker Data		Frequency Response
Tweeter	13mm polyamide hard dome	
Woofer Cone	Polypropylene	
Surround Material	Inverted rubber Surround	
Crossover Frequency	5.5 kHz	
Depth	8.25"	
Diameter of the Enclosure	9.25"	
Diameter of the Grille	12.75"	
Enclosure Mounting	Metal Swivel Clamp	
Net Weight of single speaker (Grille, Back Enclosure, and Loudspeaker)	10.0 lbs	
Shipping Weight (2 boxes of 4 speakers)	60.0 lbs	

CHANNEL ZONING ILLUSTRATION



SPEAKER CONFIGURATION *

Passive Speaker Connections:



2 position Phoenix connector for signal out to a passive speaker.

RJ 45 connection jack for PoE+


Three (3) status lights

- Power
- Dante
- Status

Dante Enabled PoE+ Amplified Speaker

2 position Phoenix connector for audio signal input from amplified speaker.

Seismic Safety Strap



Companion Speaker (1)

DS64-B INSTALLATION SCHEMATICS

Standard Ceiling Tile Bridges
(Included for all 4 speakers)

23.75"

14.0"


10.75"

Plenum Compatible
Back Enclosure
for **UL 2043** Listed for
Plenum Fire Rating.



The all-metal
swivel clamp
makes it easy to
install the
speaker
assembly to the
ceiling

The clip-on mechanism on the
grille makes it easy to install the
grille to the back enclosure. This
is AMK's revolutionary "snap-on"
grille installation system.



Guide for alignment of
enclosure to tile bridge
for grille installation

Cardboard
Paint Mask (To
be discarded
after Painting)

White Perforated
Metal Grille

12.75"


Recessed speaker baffle plate

7.0"

8.25"

9.25"

11.75"



Architect's & Engineer's Specifications

The powered loudspeaker system shall be **AMK DS82-A**. The speaker shall feature Audinate / Dante™ network audio signal that broadcasts 1 channel of audio. The speaker system shall consist of a set of 2 speakers for same channel broadcasting.

The Ethernet network must have PoE+ to provide the power that is needed for the system.

The active unit of the system shall have one RJ-45 jack for network audio connection. Then there shall be (1) one of the two position phoenix type (euro) connection. The connection shall be for the passive speaker.

The transducer in the loudspeaker system shall be AMK CX 802 coaxial loudspeaker. The woofer shall have a 20 oz. Barium Ferrite magnet. The two reproducer sections shall be coupled through a built-in capacitor bypass crossover. The crossover frequency shall be at 5.5 kHz. The low frequency reproducer shall have 1" (25.4mm) voice coil and the high frequency reproducer shall have 0.51" (13mm) voice coil.

The system shall have a frequency response of 55 Hz- 20 kHz (+/- 5dB). The power handling shall be 40watts at 8 ohm impedance. The sensitivity shall be 91dB at 1watt / 1meter.

The depth of all 2 enclosures shall be 8.25 inches. The rim diameter shall be 11.75". The enclosure diameter shall be 9.25". The depth of the enclosures shall not exceed 8.25". The system shall include 2 tie bridges. The system shall have a metal strap for attachment to a structure for seismic protection.

The total weight of the each of the speaker enclosure, tie bridge, and grille shall not exceed 9.0 lbs.


The loudspeaker system shall be AMK Innovations model **DS82-A**.

Conforms to EIA Standards: RS-276-A, RS-278-B, RS-426-A.


Polar Responses

(Measurement done in house)


250 Hz




500 Hz




1 kHz




2 kHz




3 kHz




4 kHz



8 kHz



16 kHz



Freq

Deg

250 Hz

98°

500 Hz

95°

1 kHz

55°

2 kHz

55°

3 kHz

34°

4 kHz

25°

8 kHz

65°

16 kHz

52°

Freq

Deg

250 Hz

98°

500 Hz

95°

1 kHz

55°

2 kHz

55°

3 kHz

34°

4 kHz

25°

8 kHz

65°

16 kHz

52°