

Heard Everywhere Since 1947

Model

CS650 Series

Combination VC and Selector Switch

Combination volume control and selector switch in one unit features a 50W auto transformer on the left side of a two-gang wall plate and a six-source selector switch on the right.

Features

- 50W volume control for use with 70V or 25V speaker lines provides 33dB attenuation in 10 steps. The last two steps before "Off" are 6dB (33dB total). UL Listed. Wiring connections are plug-in screw terminations for prewire convenience.
- Six-source selector switch is two-pole, non shorting rotary style to assure complete isolation between lines. Connections are Euro-style screw terminals allowing the unit to be field connected for use together or independently.
- Includes a standard or decorator style two-gang wall plate.
 Decorator models also include two single-gang plates for separate location mounting.
- The device with two-gang wall plate measures 4.562"W x 4.5"H x 2.125"D and is made to install into a two-gang or 4" square E.O. box with mud ring (not included).
- Knob and mounting screws included.

A&E Specifications

The combination volume control / source selector switch shall be Lowell Model _______. The volume control shall be a UL Listed 50W auto transformer for use with 70V or 25V speaker lines and shall provide a total of 33dB attenuation in 10 steps (the last two steps before "off" shall be 6dB). The six-source selector switch shall be two-pole, non shorting rotary style for isolation between lines. Wiring connections shall be to screw terminals allowing the unit to be field connected for use together or independently. The wall plate style shall be _____ (standard, decorator) with _____ (white, black, stainless steel, stainless steel & white, stainless steel & black) finish. The device shall install in a two-gang or 4" square E.O. box with mud ring (not included).



Standard Two Gang Stainless Steel



Decorator Style Two Gang White



Decorator Style Two Gang Black*



Decorator Style Two Gang Stainless Steel & White*



Decorator Style Two Gang Stainless Steel & Black*

Model No. Summary

Model No.	Description	Volume Control Rating	Volume Connections	Selector Switch	Selector Connections	Assembly Depth	Plate Style	Plate Color
CS650-SS	VC / Selector Switch	50W, 3dB step	Plug-in screw	Two-pole, rotary	Euro-style screw	2.125"	Standard	Stainless
CS650-DW	VC / Selector Switch	50W, 3dB step	Plug-in screw	Two-pole, rotary	Euro-style screw	2.125"	Decorator	White
CS650-DB *	VC / Selector Switch	50W, 3dB step	Plug-in screw	Two-pole, rotary	Euro-style screw	2.125"	Decorator	Black*
CS650-DSB *	VC / Selector Switch	50W, 3dB step	Plug-in screw	Two-pole, rotary	Euro-style screw	2.125"	Decorator	Stainless & Black*
CS650-DSW *	VC / Selector Switch	50W, 3dB step	Plug-in screw	Two-pole, rotary	Euro-style screw	2.125"	Decorator	Stainless & White*

^{*} Discontinued color, availability is limited.



Heard Everywhere Since 1947

Technical Drawings

