



LPD-1500S L-pad control

Wirewound L-pad control provides a constant 1500 ohm load to the line or power source regardless of control setting. Attenuation is continuous with a stop at minimum and maximum levels.

Features

- 10W audio power rating
- Continuous attenuation with stops at minimum and maximum levels
- 1500 ohm impedance
- One-gang stainless steel wall plate (2.75"W x 4.5"H) with stamped and filled dial scale
- Fluted black knob
- Mounting screws

A&E Specifications

The wirewound L-pad control shall be Lowell Model LPD-1500S, which shall provide a contant 1500 ohm load to the power source. Attenuation shall be continuous with a stop at minimum and maximum. The attached one-gang, stainless steel faceplate shall feature a stamped and paint filled dial scale, fluted black knob and mounting screws.



Model Summary

Model No.	Power Rating	Туре	Attenuation	Impedance	Wall Plate Height	Wall Plate Width
LPD-1500S	10W audio	L-pad	continuous*	1500 ohm	4.5"	2.75"

Lowell makes every effort to provide accurate information while reserving the right to change specifications and/or improve manufacturing methods without notification. ©2016 Lowell Manufacturing Company, 100 Integram Dr., Pacific MO 63069 | 800.325.9660 | www.lowellmfg.com



Technical



