



features.

- **Description:** The vandal-resistant intercom station with call switch features a heavy duty stainless steel wall plate and vandal-resistant screws with driver bit. It's ideally suited for areas where vandalism is a concern, such as correctional facilities, public garages, lobbies, warehouses, and similar areas.
- **Construction:**
 - Heavy duty 11-gauge stainless steel wall plate, brushed finish.
 - 2-gang or 3-gang
 - Shallow depth (mounts in standard 2-gang or 3-gang box)
 - Includes vandal-resistant hardware (Torx head screws and driver bit) for a high degree of security.
 - Internal offset baffles provide added protection from vandalism.
- **Transformer:**
 - 25V line 1W, 1/2W
 - Pigtail connections
- **Call Switch:**
 - SPST (single pole, single throw)
 - Rating: 1A 48VDC
 - Function: Momentary (normally open)
 - Screw terminal connections
- **Optional:**
 - **#PHB-2:** 2-gang protective hooded box is 11-gauge steel with gray finish. 4.50"H x 4.625"W x 4.00"D.
 - **#P1X Series:** 2-gang or 3-gang surface-mount wall box, 20-gauge steel with white finish and rear/side knockouts.
- **Speaker:**
 - 45ohm, 6W, 98dB @1W, 300Hz-8kHz
 - Moisture resistant
 - Pigtail connections for easy field installation
 - For clear 1-way or 2-way communication

a&e specifications.

The vandal-resistant intercom station with call switch shall be Lowell _____ (#VRIC-2G-4525, #VRIC-3G-4525), which shall feature a 45ohm speaker with 25V transformer and push button call switch. The intercom station shall have a _____ (2-gang, 3-gang) wall plate, 11-gauge stainless steel with brushed finish. The unit shall feature offset baffles and include vandal-resistant screws and a driver bit.

Optional

- The intercom shall include a protective hooded surface-mount wall box, Lowell #PHB-2, which shall be 11-gauge steel with gray finish.
- The intercom shall include a _____ (2-gang, 3-gang) surface-mount, wall box with white finish, Lowell _____ (#P1X-2, #P1X-3).

VRIC Series summary

Model No.	Description	Wall Plate	Speaker	Transformer	Height	Width	Depth
VRIC-2G-4525	Intercom station with call switch	2-gang	45 ohm	25V	4.5"	4.47"	1.75"
VRIC-3G-4525	Intercom station with call switch	3-gang	45 ohm	25V	4.5"	6.375"	1.75"