Live Sound Instruments Bass Instruments

- P2:
- Dynamic microphone designed for low-pitched instruments
- Powerful sound with enough bass range
- P2 & 4:
- Handles highest sound pressure levels
- Integrated stand adapter and (P4) external bracket
- Response tailored for neutral reproduction of instrument sounds
- Rugged all-metal body withstands typical tough stage use
- · Humbucking coil rejects EMC noises



Perception live

The P2 is a rugged all metal microphone for bass instruments such as a bass drum, trombone or bass amplifier. It delivers powerful sound with a high energy low end.

The P4 microphone with its solid metal case will stand up to typical stage use. An integrated stand adapter makes the mounting procedure easy and both microphones include a black carrying case.

P2		P4	
Polar pattern	cardiod	Polar pattern	cardiod
Frequency range	20-16,000 Hz	Frequency range	40-18,000 Hz
Max. sound pressure level	157 dB SPL	Max. sound pressure level	152 dB SPL
Sensitivity	2.3 mV	Sensitivity	2.4 mV
Impedance	400 ohms	Impedance	500 ohms
Net/shipp. weight	400/450 g	Net/shipp. weight	200/240 g
Finish	stage black	Finish	stage black
Product dimensions	130*132**60 mm	Product dimensions	110*79*44 mm
Standard accessories	black carrying case	Standard accessories	H 440, case
Item number	3100H00150	Item number	3100H00130



PERCEPTION *live*

Lead Vocals Live Sound Backing vocals Instruments

- P3 & P5/ P5 S:
- Rugged performance microphone designed for vocals
- Rugged wire mesh cap with internal windscreen
- Die-cast metal body
- · Complete with stand adapter and zipp-bag



Perception live

The P3 microphones are ideal for backing vocals, guitar, wind instruments and many other applications. Metal case and wire mesh grill for exceptional ruggedness.

The P5/P 5S are dynamic handheld microphones for lead vocalists. The super cardioid polar pattern guarantees for utmost gain before feedback and makes the voice cut through the mix more easily. Its heavy duty metal body will take some tough handling. This microphone is available with or without on/off switch.

P3		P5/P5 S	
Polar pattern	cardiod	Polar pattern	
_	40.00.000.11	_	

Frequency range 40-20,000 Hz

Max. sound pressure level 144 dB SPL

Sensitivity 2.5 mV

Impedance 600 ohms

Net/shipp. weight 260/300 g

Finish stage black

Standard accessories stand adapter, SA 45

190*51 mm

Item number 3100H 0140

supercardiod 40-20,000 Hz Frequency range Max. sound pressure level 144 dB SPL 2.5 mV Sensitivity Impedance 580 ohms Net/shipp. weight 200/240 g Finish stage black **Product dimensions** 190*51 mm Standard accessories stand adapter, SA 45

Item Number P 5 3100H0110

Item Number P 5 S 3100H00120

www.akg.com

Product dimensions

AKG Acoustics GmbH

Lemböckgasse 21–25, 1230 Vienna / AUSTRIA, phone: + 43 1 86654 0 e-mail: sales@akg.com

AKG Acoustics, U.S.

8400 Balboa Boulevard, Northridge, CA 91329, U.S.A., phone: + 1 818 920 3212 e-mail: akgusa@harman.com

For other products and distributors worldwide visit www.akg.com Specifications subject to change without notice.

