



Description

The Rockustics BlockRock speaker from SoundTube is a premium 2-way outdoor loudspeaker solution. The Monument series speakers are designed to provide a full 360 degrees of audio coverage. The cabinets are made of weather-resistant stone and resin compound designed to withstand rain, frost, snow and ice.

Features

- Coaxial driver assembly with 6.5-inch (165.1 mm) polypropylene woofer and 0.75-inch (19mm) mylar dome tweeter delivering 360° of dynamic audio
- UV-, scratch-, chlorine- and weather-resistant enclosure with professional-grade components for long-lasting performance and durability
- Constructed of non-polluting stone and resin compound
- Color options: Slate or Marble
- Optional accessories: 64 W, 70.7/100 V transformer (TF-WS64-70)

BlockRock PRODUCT SPECIFICATIONS

System Type	6.5" Omnidirectional Outdoor Monument Series Speaker
Impedance (Nominal) ¹	8 ohms
Sensitivity dB @ 2.83 V / 1 M	92 dB
Sensitivity dB @ 1 W / 1 M ²	89 dB
Frequency Response (±3 dB) ³	76 Hz - 19.5 kHz
Frequency Response (±10 dB) ³	65 Hz - 20 kHz
Max. Program Power ⁴	140 W
Max. Continuous Power RMS ⁵	70 W
Max. SPL dB @ 1 M ⁶	107.4 dB
Tap Selector	Wire leads with optional transformer
Transducer: Low-Frequency Driver	6.5" Weather Resistant Polypropylene
Transducer: High-Frequency Driver	.75" Mylar Dome
Enclosure Material	Stone and resin compound
Grille	Screen mesh cover
Inputs	Wire leads
Colors	Slate or Marble
Length	13.2 in / 335.28 mm
Width	13.2 in / 335.28 mm
Height	16.45 in / 417.83
Shipping Weight	29 lbs.
Packaging	One per box
Included Accessories	Wire Nuts
Optional Accessories	64 W Transformer (TF-WS64-70) Security Bracket (RSB1)
Certifications	CE, RoHS
TAA Compliant (Trade America)	Yes
BAA Compliant (Made in USA)	Yes

¹ Impedance listed per IEC 60268-5 with a minimum less than 80% the nominal impedance

² 1 W/1 M sensitivity determined using nominal impedance

³ Frequency response measured in half or full space as dictated by speaker mounting configuration

⁴ Max program power is 3 dB above max continuous power

⁵ Continuous power rating, EIA-426-B test

⁶ Max output based on max continuous power

SoundTube®

13720 W. 109th St.
Lenexa, KS 66215
Phone: 913.663.5600
Fax: 913.663.3200
Toll Free: 855.663.5600
www.soundtube.com

