

### PRODUCT DESCRIPTION

The DS1398 contains dual, horizontally opposed speakers which produce uniform sound dispersion ideally suited for reverberant under floor cavities and ceiling plenums. An optional mounting bridge is available for use in ceiling plenums where conventional sound masking speakers are not applicable (specify DSSSB-4).

### FEATURES

- For use in floor cavities as shallow as 1-3/4"
- Optional bridge mount for use in ceiling plenums
- Performance-engineered dual drivers with tuned ports well suited for sound masking produce uniform 360-degree dispersion
- ETL listed to conform to UL1480 and CSA C22.2 60065



### TECHNICAL SPECIFICATIONS

<b>Loudspeaker:</b>	Dual horizontally opposed high performance drivers
<b>Impedance:</b>	4 ohms nominal
<b>Dimensions:</b>	5.25 inches x 6.25 inches x 1.80 inches tall
<b>Weight:</b>	1.75 lbs.
<b>Power Rating:</b>	10 Watts

### ARCHITECTURAL SPECIFICATIONS

Sound masking speaker assembly shall be Dynasound model DS1398. Unit shall contain dual horizontally opposed loudspeakers, with dual internal acoustical chambers. The unit shall be factory assembled, wired and ready for installation. Strain relief shall be provided to protect hook-up leads. The enclosure shall measure 5.25 inches by 6.25 by 1.80 inches tall. Speaker shall be UL listed to conform to UL1480, UL2043 and CSA 60065.