

DATA SHEET



2-Port HDMI® Splitter - 4K 60Hz

Split a single HDMI audio/video signal from a source device to two HD displays

OVERVIEW

The 2-Port HDMI Splitter - 4K 60Hz is a 1-input 2-output splitter supporting up to 4K (3840 x 2160 at 60hz, 4:4:4) video, ideal for applications utilizing the HDMI 2.0 standard. A perfect solution for connecting a computer, Blu-ray™ player, gaming console, media server, or A/V receiver to two HDMI displays.

The HDMI splitter is HDCP 2.2 compliant and supports exceptional 4K UltraHD resolution up to 3840 x 2160 at 60hz with 4:4:4 chroma sub-sampling, handling total HDMI data rates up to 18Gbps.

FEATURES

- One input and two outputs
- Supports resolutions up 4K (3840 x 2160 at 60hz, 4:4:4)
- HDMI 2.0 standard
- HDCP 2.2 compliant
- Supports 3D and EDID management
- 5V, 2A power supply

ITEM DESCRIPTION

41394 2-Port HDMI® Splitter - 4K 60Hz

DATA SHEET

SPECIFICATIONS: 2-Port HDMI® Splitter - 4K 60Hz

ELECTRICAL SPECIFICATIONS:

- Output Video: HDMI 2.0
- Power Consumption: 2W
- Power Supply: 5V DC
- Input Video Signal: 0.5-1.0V p-p
- Input DDC Signal: 5V p-p (TTL)
- Video Format Support: Up to 4Kx2K (3840 x 2160)
- Bandwidth: 18Gbps

PHYSICAL SPECIFICATIONS:

- Operating Temperature: -5 to +35°C
- Operating Humidity: 5 to 90% RH (no condensation)
- Splitter Dimensions (HxWxL): 23.5 x 75 x 111mm
- DC Cord: 20AWG, 300V, L=1500+/-100MM
- DC Plug Dimensions: 5.0 x 2.1 x 10mm
- DC Adapter Block Dimensions: 65.85 x 42.60 x 30mm
- With interchangeable plug (US type or UK type)



- 1.HDMI A 19 pin female input /output connector, gold plated,15U"
- 2.DC 5V power jack
- 3.Input and output LED indicate (white)
- 4.EDID

C2G[®]
A brand of **legrand**

6500 Poe Avenue
Dayton, OH 45414
Phone: 800.CABL.911
www.c2g.com

Follow Us

