

IPD-TSB2.0

STNet® Dante-Enabled Soundbar

An ultra-thin 2-way Dante-enabled digital end-point solution in a soundbar configuration. The Soundbar brings Dante connectivity from end to end in conferencing and video installations. Measuring only 1.5 inches thick where the bar meets the TV, it incorporates a right and left speaker with four 3-inch ultra-long throw polypropylene woofers with NBR surrounds, four bass radiators, and two 0.75-inch synthetic soft dome tweeters.

- Flat Panel Dante 2-Channel Soundbar
- IP Addressable
- Dante and AES67 Compatible
- PoE Powered
- 100dB Max Output
- Configurable with onboard DSP
- Micro-controlled monitoring of speaker functions
- Ideal Applications:
 - Conference rooms
 - Classrooms
 - Boardrooms



Description	2-Way Ultra-Thin Powered Dante Soundbar
Recommended Power	PoE, PoE+, (STNet) 40W PoE, or 24V barrel connector
Max. SPL @ 1M	100dB
Tweeter	Two 0.75" Silk/Synthetic Soft-Dome
Woofer	Four 3" Polypropylene w/ NBR Surround
Bass Radiator	Four 3" Polyproylene w/ NBR Surround
Inputs	RJ45
Grille	Black Powder-Coated Pressure-Fit Aluminum
Height	6.75 in
Width	43.0 in
Depth	2.5 in (1.5 in where the Soundbar meets the TV)
Included Accessories	Wall-Mount and Table-Mount Hardware