



Configuration:

LS-47-216 Listen Premiere Level I Stationary RF System (216 MHz)
 LS-47-072 Listen Premiere Level I Stationary RF System (72 MHz)

Product Overview:

Get your smaller venue started with assistive listening technology right away by installing the LS-47 Premiere Level I Stationary RF System. Complete with the 216 MHz version of our LR-400 Digital Display Receivers, the LS-47 provides listeners with a compact, convenient receiver that includes channel selection, battery level, and signal strength information shown right on the device screen.

The included LT-800-216 Stationary RF receiver and LA-102 telescoping provide excellent reception and signal clarity at a range of up to 228.6 m (750 ft.). Additionally, ear speakers, neck loops, alkaline batteries, and more are included to make getting started with assistive listening simple and fast.

Highlights:

- Stationary transmitter and four (4) digital display receivers for the 216 MHz band included
- Complete with signage, ear speakers, and more
- Offers 57 digital channels to choose from
- Digitally tuned receivers ensure reliable signal

Includes:

- One (1) LT-800-216-01 RF Transmitter (216 MHz)
- One (1) LA-102 Telescoping Top Mounted Antenna (216 MHz)
- Four (4) LR-400-216 Portable Display RF Receiver (216 MHz)
- Four (4) LA-164 Ear Speaker
- Two (2) LA-166 Neck Loop
- One (1) LPT-A107-B Dual RCA to Dual RCA Cable 2 m (6.6 ft.)
- Four (4) LA-361 High Capacity AA Alkaline Batteries (2)
- One (1) LA-304 Assistive Listening Notification Signage Kit

Product Specification: Listen Premiere Level I Stationary RF System (216 MHz)	
Physical	
Shipping Weight	10.0 (4.5)