

C8


Pure Resonance Audio C8 8" 70 Volt Commercial Ceiling Mount Speaker

DESCRIPTION

The Pure Resonance Audio C8 is an 8" 2-way high-performance ceiling mount loudspeaker. This 70V ceiling speaker delivers full-range high-quality sound for background and foreground music or paging in commercial environments. With a built-in 60-watt 70-volt transformer and an 8-ohm bypass, the C8 is perfect for various applications, including business offices, retail stores, restaurants, classrooms, and conference rooms. The ABS enclosure with an iron back can contains an 8" paper woofer and a 1" silk tweeter.


FEATURES


- Seamlessly blends into the ceiling with the bezel-less magnetic grill
- \cdot 70 Volt / 100 Volt transformer with 8Ω bypass
- Power tap switch located on the front of the speaker for easy access
- · 94dB sensitivity provides powerful quality sound
- Wide frequency range and 60 Watt power handling capability
- · 8" Woofer and 1" tweeter
- · Recessed 4-pin Euroblock screw terminal connector




PRODUCT SPECIFICATIONS	
RMS Power Rating	60 Watt
Frequency Response	55Hz - 20kHz
Impedance	8 Ohms
Transformer Taps	3.75W, 7.5W, 15W, 30W, 60W @ 70V 7.5W, 15W, 30W, 60W @ 100V
Low-Frequency Driver	8" Woofer
High-Frequency Driver	1" Silk driver
Speaker Cone Material	Paper
Sensitivity SPL	94±3dB @ 1W/1 m
Material	ABS, iron back barrel, and powder-coated iron mesh grill
Cutout Size	11.5" (292 mm)
Dimensions (Dia x D)	12.6" (320 mm) x 9.65" (245 mm)
Weight	11.68 lbs (5.3 kg)
Shipping Dimensions	14.96" (380 mm) x 14.96" (380 mm) x 13.19" (335 mm)
Shipping Weight	17.2 lbs (7.8 kg)


DIMENSIONS





IMPEDANCE VS FREQUENCY






DI

6.0 7.2

SPL VS ANGLE



(866) 676-7804 sales@pureresonanceaudio.com www.PureResonanceAudio.com