

PMZ16

Pure Resonance Audio PMZ16 Remote Paging Microphone Station with Zone Control and Chimes

DESCRIPTION:

The PMZ16 remote microphone station with 16" gooseneck condenser microphone is capable of paging a single zone, group of zones, and/or all zones. The PMZ16 paging microphone station can also be connected to the Pure Resonance Audio RZMA120BT multi-zone mixer amplifier, with the maximum shielded CAT5 length between microphone paging station and mixer amplifier not exceeding 500 feet. This microphone station can be daisy-chained (4 max) via shielded Cat5 for zone paging and chimes (1-4).

FEATURES:

- · 4 zone remote paging microphone
- · With zone, group zone and all zone paging capacity
- · Supports up to 4 microphones on one amplifier
- Microphone connects to the amplifier through sheilded CAT 5 cable
- Microphone is DC24V powered by the amplifier at max 500' distance
- Built-in 2 & 4 tone chime selector for pre-announcement
- · Built-in microphone, chime & master volume control
- · 10 segments level meter to display output level
- Online function and an online interface for LINK IN LINK OUT
- · Built-in independent switching power supply



PRUDUGI SPECIFICATIONS:	
Microphone Type	Condenser
Power Input	24 Volts DC
Interface Connection	Sheilded CAT5
Daisy Chain Communication	Max Length 500'
Power Supply	DC 24V
Output Level	1V/600 Ohms
Frequency Response	80 - 18KHz (±3dB)
THD	<1%
Power Consumption	10W
Weight (without Microphone)	2.12 lbs (0.96 kg)
Weight (with Microphone)	2.3 lbs (1.04 kg)