

PVX™ 10



OVERVIEW

The PVX™10 is a two-way sound reinforcement system based on a heavy-duty 10" woofer and a RX™10N titanium diaphragm dynamic compression driver mounted on a 100 by 60 degree coverage Quadratic Throat Waveguide™. Its sleek modern appearance coupled with excellent performance offer an outstanding package.

FEATURES

- Two-way sound reinforcement enclosure
- Crossover network for driver protection and EQ
- High frequency driver protection
- Durable plastic injection-molded trapezoidal enclosure
- Asymmetrical horn aims the sound down 10 degrees, at the audience, not over their heads
- Full-coverage heavy-duty perforated steel grilles, with powder coat finish
- Pole mount molded-In
- Top and bottom flying point inserts
- Patented Quadratic Throat Waveguide™ technology, 100 by 60 degree coverage
- 400W program/800W peak power handling
- RX™ 10N compression driver, with 1.0 inch titanium diaphragm
- 10" heavy-duty woofer with 2 3/8" voice coil & 50 oz. magnet
- Extra angled section on right side allows floor monitor use
- Weight Unpacked: 24.91 lb(11.3 kg)
- Weight Packed: 32.19 lb(14.6 kg)
- Width Packed: 16.142"(41.00068 cm)
- Height Packed: 22.44"(56.9976 cm)
- Depth Packed: 14.174"(36.00196 cm)