

<b>CONSTRUCTION DATA</b>	
<b>Conductor:</b>	
# of Conductors	2
AWG	14
Conductor Stranding	19x27
Copper Type	Bare
<b>Insulation:</b>	
Type	Plenum PVC
Thickness	0.012 in.
Color Code	BK, RD
<b>Shield:</b>	
Shield Type	N/A
Drain Wire Type	N/A
<b>Jacket:</b>	
Jacket Type	Plenum PVC
Thickness	0.015 in.
Nominal Cable O.D.	0.223 in.
Colors	BK, WH

<b>APPLICATIONS</b>	
Audio	
Control	
Low Voltage Power	

<b>X-REFERENCE</b>	
WPW	25226B,*226
Belden	6100UE

<b>WATER OTTER VERSIONS</b>	
Water Block	WB2C14GY
Direct Burial	DB2C14BK

<b>CABLE PRINT LEGEND</b>	
Provideon Wire & Cable #2C14P 2/14 Unshielded CL2P Audio Cable Date Code A B C D E F G H I J 1 2 3 4 5 6 7 8 9 0	

<b>TECHNICAL DATA</b>	
Voltage Rating	150 V
Operating Temperature	0 to 75 C
Flame Test	NFPA 262 Plenum
NEC Rating	CL2P
RoHS Compliant	Yes
Max. Pull Tension	84 lbs
Max. Bend Radius	2.007 in
Cable Weight	36 lbs
Nominal DCR	2.7 Ohms/1000 Ft.
Nominal Cap. Between Conductors	36 pf/ft
Nominal Cap. Cond. To Shield	N/A

