

## CONSTRUCTION DATA

<b>Conductor:</b>	
# of Conductors	2
AWG	22
Conductor Stranding	7x30
Copper Type	Bare
Nominal Resistance	17.5 Ohms/1000 Ft.

<b>Insulation:</b>	
Type	Plenum PVC
Thickness	0.007 in.
Color Code	BK, RD

<b>Shield:</b>	
Shield Type	Overall 100% AL Foil
Drain Wire Type	Tinned Copper
Nominal Cap. Between Conductors	54 pf/ft
Nominal Cap. Cond. To Shield	97 pf/ft

<b>Jacket:</b>	
Jacket Type	Plenum PVC
Thickness	0.015 in.
Nominal Cable O.D.	0.116 in.
Colors	BK, WH

## APPLICATIONS

Audio
Control
Low Voltage Power

## X-REFERENCE

WPW	25291B, *291
Belden	6500FE

## WATER OTTER VERSIONS

Water Block	WB2C22SGY
Direct Burial	Call Engineering

## CABLE PRINT LEGEND

Provideon Wire & Cable #2C22PS 2/22 Shielded CMP Audio Cable Date Code A B C D E F G H I J 1 2 3 4 5 6 7 8 9 0

## TECHNICAL DATA

Voltage Rating	300 V
Operating Temperature	0 to 60 C
Flame Test	NFPA 262 Plenum
NEC Rating	CMP
RoHS Compliant	Yes
Max. Pull Tension	28 lbs
Max. Bend Radius	1.044 in.
Cable Weight	11 lbs

