



## MMD 935 | MMD 945 | MMK 965 Microphone Heads



Designed for use with the ew G4 and ew G3 hand-held radio microphones, the microphone heads of the MMD 900 microphone head series have the same excellent acoustic properties as the wired e900 series microphones.

The MMD 935 is specially designed to perform under pressure while cutting through the mix with its high output.

The MMD 945 is specially designed to ensure vocals cut through the mix and to provide an extremely vivid, crisp sound with drums and percussions.

The MMK 965-1 is a fully professional true condenser microphone. The switchable pick-up pattern (cardioid/super-cardioid) provides excellent flexibility and enables the MMK 965 to handle the highest signal levels without feedback.

### SPECIFICATIONS

#### MMD 935-1

Transducer principle	dynamic
Sensitivity	2.5 mV/Pa
Sound pressure level	154 dB SPL
Pick-up pattern	cardioid

#### MMD 945-1

Transducer principle	dynamic
Sensitivity	1.8 mV/Pa
Sound pressure level	154 dB SPL
Pick-up pattern	supercardioid

#### MMK 965-1

Transducer principle	extern polarisiertes Doppelmembran-Kondensatormikrofon
Pick-up pattern	cardioid/supercardioid, switchable
Sensitivity (free field, no load) (1 kHz)	7.0 mV/Pa
with preattenuation	2.2 mV/Pa (factory setting)
Max. SPL at 1 kHz	144 dB
with preattenuation	154 dB (factory setting)
Dynamic range	126 dB(A)
Diameter of diaphragm	2.54 cm (1")
Frequency response	40 to 20,000 Hz
"Equivalent noise level A-weighted (DIN IEC 651)"	18 dB
Weight	162 g

### PRODUCT VARIANTS

<b>MMD 935</b>	black	Art. no. 502577
<b>MMD 935 BL</b>	blue	Art. no. 502578
<b>MMD 945 BK</b>	black	Art. no. 502579
<b>MMD 945 BL</b>	blue	Art. no. 502580
<b>MMK 965-1 BK</b>	black	Art. no. 502582
<b>MMK 965-1 BL</b>	blue	Art. no. 502583
<b>MMK 965-1 NI</b>	nickel	Art. no. 502584