

BluePOD Solo

Bluetooth Integration Hub



Integrate Bluetooth technology with your current audio system setup with the BluePOD Solo. Easily connect audio from your personal device, such as a phone or laptop, to your room's audio system, while still using your existing audio system's capabilities.

BluePOD Solo (AP BP2)

Dimensions:	7"W x 3.75"D x 1.5"H (178 cm x 95 cm x 38 cm)
Power Supply:	Input: AC Power Socket; TFP 062; 100-240 VAC, 50-60 Hz International Desktop Power Supply with IEC Line Cords Output: 24VDC @ 0.75A DC 2.5 mm ID barrel plug
Bluetooth Wireless Access Point:	Bluetooth 4.2 with aptX HD Support; Connect with shielded CAT5e or CAT6 cable.
Bluetooth Wireless Access Point Chassis:	Wall or ceiling mount type, molded plastic, white top, grey bottom
Controller Chassis:	Desktop type, black, metal with white and red legends on front, white legends on back.
Inputs:	Balanced, +4 dBu Line In (3 pole Phoenix style connector); Dante Optional
Bluetooth Range:	50 ft radius (15.24 m)
Outputs:	Balanced/Unbalanced, +4 dBu Line out (3 pole Phoenix style connector); Dante Optional
Optional Dante:	Available in AP BP2 D Model
RS-232 Control:	3 pole Phoenix style connector
Operating Environment:	32°F to 104°F (0°C to 40°C) with 0-90% relative humidity. Storage: -40°F to 150°F (-40°C to 65°C)
Warranty:	2-year parts and labor
Approvals:	CE, FCC, Industry Canada, RoHS3, WEEE, RCM, PSE

Architecture and Engineering Specifications

- The Blue POD Solo, model number AP BP2, shall be housed in a black metal enclosure.
- The AP BP2 shall include a Bluetooth Wireless Access Point (B-WAP) offering a 50ft radius Bluetooth range from the B-WAP.
- The AP BP2 shall have a three-pole Phoenix style connector for professional line level audio input.
- The AP BP2 shall have a three-pole Phoenix style connector for professional line level audio output.
- The AP BP2 shall have a three-pole Phoenix style connector for RS-232 Control.
- The AP BP2 D shall have a Dante port.
- The AP BP2 shall be covered by a two-year parts and labor warranty.
- This device shall be the Williams Sound model AP BP2.



Dante port only present on AP BP2 D models.

Domestic Sales

Williams AV
10300 Valley View Rd
Eden Prairie, MN 55344
Ph: 800-328-6190 / 952-943-2252
Fax: 952-943-2174
Email: info@williamsav.com
Web: www.williamsav.com

International Sales

International Sales Department
Williams AV
10300 Valley View Rd
Eden Prairie, MN 55344 USA
Phone: +1 952 943 2252
Fax: +1 952 943 2174
Email: info@williamsav.com
Web: www.williamsav.com

WILLIAMS AV
info@williamsav.com / www.williamsav.com
800-843-3544 / INTL: +1-952-943-2252