



## MP-A Series

### MP-A20V | MP-A40V | MP-A80V

Multi-channel amplifiers



## Features

- FlexAmp Technology - every pair of channels share a 400 W power supply. Each channel is capable of delivering the full power or sharing it in any ratio
- Class-D output circuitry and switchmode power supply for high efficiency and low cost of ownership
- 1RU amplifier design for rack space savings
- Load selector for driving 4  $\Omega$ , 8  $\Omega$ , 70 V or 100 V on each channel
- Selectable 80 Hz highpass filter offered on each channel
- Power saving features - Auto-standby (after 28 minutes with seamless auto-ramp when signal returns) and remote standby input
- Amp status remote output
- Legacy of rock-solid QSC amplifier dependability

## Introduction

The MP-A Series music and paging amplifier family builds on a 50 year legacy of QSC amplifier dependability and quality while offering an incredible amount of flexibility for business music and paging applications.

### FlexAmp Technology

FlexAmp Technology, which is the driving force behind all three models in the series, provides each pair of channels a combined power of up to 400 W, which can be shared in any ratio between them. MP-A20V shares 400 W across both channels. MP-A40V offers two sets of channel pairs, each of which shares 400 W for a total of 800 W, MP-A80V provides an incredible 1600 W with four sets of channels pairs, each channel pair shares 400 W. This makes for an amazing amount of flexibility, especially when paired with the output mode switch that offers settings for 4  $\Omega$ , 8  $\Omega$ , 70 V and 100 V.

Additional capabilities of the MP-A series include an 80 Hz highpass filter available on each output, as well as a remote input for putting the amplifier into standby mode for fire safety systems and an amplifier status signal on the remote output for system verification.

## Flexibility

For an example of versatility of the MP-A Series, imagine the MP-A40V in a typical restaurant scenario. Output A of the amplifier is set up for a 20 W 70 V load for a pair of ceiling loudspeakers in the bathrooms while output B is set up in 4  $\Omega$  mode for driving one or two Lo-Z subwoofers with up to 380 W. Output C is set up with the highpass filter engaged for driving 250 W into 70 V ceiling loudspeakers in the main dining room, while output D is driving 150 W into 8  $\Omega$  surface-mount loudspeakers on the patio.

## Power and Space Efficiency

MP-A Series amplifiers are extremely efficient with class-D output circuitry and switchmode power supplies. In addition, all models offer seamless Standby mode when not in use for 28 minutes and auto-ramp circuitry that ensures quiet and fast power up from Standby when signal is present. This combination of output topology and energy saving circuitry make for extreme efficiency and low operational costs. The 1RU chassis means that the MP-A Series amplifiers are perfect for installations with rack space restrictions.

# MPA Series

Model	MP-A20V	MP-A40V	MP-A80V
Channels	2	4	8
<b>Power (all channels driven)</b>			
8 $\Omega$	200 W	200 W	200 W
4 $\Omega$	200 W	200 W	200 W
70 V	200 W	200 W	200 W
100 V	200 W	200 W	200 W
FlexAmp technology	400 W for a pair of adjacent channels (1-2, 3-4, 5-6, 7-8)		
Frequency response	20 Hz – 20 kHz +/- 0.5 dB		
Signal to noise	> 103 dB		
Input sensitivity	1.23 V (+4 dBu)		
Gain at 8 $\Omega$	30.0 dB		
Output circuitry	Class D		
Input impedance	>10k, balanced or unbalanced		
Maximum input level	12.3 V (+24 dBu)		
<b>Cooling</b>			
Type	Forced air cooling		
Operating temperature range	Maximum: -10° - 50° C, recommended: 0° - 35° C, reduced performance above 40° C		
<b>Connectors</b>			
Input connectors	Two 3.5 mm Euro, 3-pin (green)	Four 3.5 mm Euro, 3-pin (green)	Eight 3.5 mm Euro, 3-pin (green)
Remote connectors	One 3.5 mm Euro, 5-pin (black)	One 3.5 mm Euro, 5-pin (black)	One 3.5 mm Euro, 5-pin (black)
Output connectors	One 5.0 mm Euro, 4-pin (green)	Two 5.0 mm Euro, 4-pin (green)	Four 5.0 mm Euro, 4-pin (green)
Front panel indicators	Power, signal (per channel), limit / mute / protect (per channel)		
Rear panel indicators	Bi-Color LED signal / limit / mute / protect		
User-configurable operating modes (per channel)	DIP switch selectable, low impedance 4 $\Omega$ or 8 $\Omega$ , high impedance direct drive 70 V or 100 V		
Remote I/O	Remote standby, amplifier status enunciation on 3.5 mm connectors		
Highpass filter	80 Hz DIP switch engaged per channel		
Dimensions (HWD) inches	1.75 in x 19 in x 13.6 in		
Dimensions (HWD) mm	44 mm x 483 mm x 345 mm		
Net weight	7.7 lb (3.5 kg)	9.3 lb (4.2 kg)	12.8 lb (5.8 kg)
Shipping weight	12.3 lb (5.6 kg)	13.9 lb (6.3 kg)	17.4 lb (7.9 kg)

Specifications subject to change without notice.



1675 MacArthur Boulevard • Costa Mesa, CA 92626 • Ph: 800/854-4079 or 714/957-7100 • Fax: 714/754-6174

© 2018 QSC Audio Products, LLC. All rights reserved. QSC and the QSC logo are registered trademarks of QSC Audio Products, LLC in the U.S. Patent and Trademark office and other countries. MPA Spec Sheet 05252018

