



## Features:

- 100 Watt Active Mini Series Speaker
- ⊃ 90° x 90° HF Driver
- S-inch Woofer with 1-inch Mylar Dome Tweeter
- Includes U-bracket For Mounting
- ⊃ 60 to 20,000 Hz Frequency Response
- ⊃ 1 x 1/4-inch Inputs / 1 x 1/4-inch Outputs
- ⊃ Injection Molded, ABS Plastic Cabinet Construction
- Two-year Unconditional Warranty\*

\*Warrany valid in Canada and the United States only



## **Overview:**

The C170P is a powered version of the C170, which is based on the already popular C110, C120 and C130, which have a complete list of features that make them an extremely good value for fixed installations. The C170P, is a compact 100 watt powered loudspeaker made from an ABS plastic enclosure with an 8-inch driver and 1-inch Mylar tweeter, and features 1/4" input and output connectors for maximum versatility.

The trapezoidal shape makes the C170P ideal for install or array mounting in tight locations. Shipped with a rugged U-bracket for wall or ceiling mounting, they are a very versatile and cost-effective solution where superior sonic quality is required for small installations, or as a repeater or fill cabinet in larger venues. An optional polemount adapter (C170ADAPT) is also available for applications where placing the C170P on a speaker stand is required.

Exclusive features to the C170P include a 1/4" input and auxiliary out, controls for Gain, Volume and Tone, with a switchable mic/line input sensitivity, and a power switch.



Model	C170P
SYSTEM TYPE	2-Way
ACTIVE OR PASSIVE	Active
IMPEDANCE	N/A (Active)
SENSITIVITY (dB @ 1W / 1M)	N/A (Active)
PROGRAM POWER (watts)	100
MAXIMUM SPL (dB)	113
FREQ. RESPONSE (Hz +/- 3dB)	60 - 20000
DRIVER CONFIGURATION	8" / 1" dome tweeter
HF DRIVER(S)	1" Mylar Dome Tweeter
LF DRIVER(S)	8"
TOTAL POWER (watts)	100
COOLING SCHEME	Heat Sink
POWER CABLE	Built-in
POWER SWITCH	Yes
INPUTS	2 x 1/4" TRS (Input/Aux Out)
INPUTS - 1/4" Jacks	1 x TRS
MIXER CONTROLS	Mic/Line sensitivity switch Gain,
	Tone, Volume controls
OTHER CONTROLS / FEATURES	Switchable AC voltage 115/230
FEET	Yes
INCLUDED HARDWARE	Mounting Bracket
OPTIONAL HARDWARE	Pole Mount Adaptor (1 3/8''-3.5cm)
	(C170ADAPT)
ENCLOSURE MATERIALS	ABS Plastic
OPTIONAL FINISH	-
GRILLE	Perforated Metal
DIMENSIONS (DxWxHxBW inches)	11.25 x 9.75 x 16.25 x 9.5
DIMENSIONS (DxWxHxBW cm)	28.5 x 25 x 42 x 24
WEIGHT (lbs/kg)	18.7 / 8.5