



Cooler By Design™

Blizzard Lighting, LLC

Phone: 1.866.493.6025 Fax: 1.866.870.0031

Email: info@blizzardlighting.com Website: http://www.blizzardlighting.com

6* 10-Watt CREE™ RGBW Moving Head

Snake Eyes™ Mini is the "fun sized" version of our larger Snake Eyes™ moving head fixture that is loaded with 6* CREE® 10W RGBW LEDs, each with a 9° beam angle. A bonus of 12* RGB strips beautifully highlight each edge of the head, and can perform color chases in auto mode or be controlled via DMX with a separate dedicated strip chase speed control channel.

Aerial effects from Snake Eyes™ Mini moving head fixtures are crisp and bright with RGBW mixed colored beams coming from any or all directions with user-selectable 630°/540° pan, and never-ending infinite tilt. And just like our larger Snake Eyes™ fixtures, this little guy still offers a "wow factor" that is off the charts (for a price that's not)!

Snake Eyes™ Mini has two user-selectable DMX modes (14/16-channels) that allow ease and flexibility in programming, as does its easy-to-use 4-button LED control panel. Power connection is via industry standard PowerCon® compatible In/Out jacks, and DMX 3-pin In/Out jacks + a single quarter-turn "Omega" quick connect type clamp bracket round out the pro feature set.

And as course, Snake Eyes™ Mini is backed by Blizzard's 2-year warranty.

Main Features

- 6* 10W CREE® RGBW 4in1 LEDs, 50,000 hours
- 12* DMX controllable RGB strips
- 630°/540° pan, infinite tilt
- User selectable 14/16-channel DMX modes
- Built-in auto/sound active programs
- 0-100% linear LED dimmer
- Pan/tilt invert
- 1-25Hz strobe
- 3-pin male and female DMX In/Out
- PowerCon[™] compatible AC power In/Out

Warranty

• 2-year limited warranty, does not cover malfunction caused by damage to LEDs.









Light Source

- 6* 60W CREE® RGBW 4in1 LEDs, 50,000 hours
- 12* controllable RGB strips

Control

- Protocol: USITT DMX-512
- DMX Channels: 14/16-channels
- · Standalone, Master/Slave, Auto, & Sound Active
- 3-pin DMX input/output
- Easy-to-use, 4-button LED control panel

Optical

- Beam Angle: 9 degree
- · Luminous Intensity: 1,521 Lux @ 2M

Power

- Operating Voltage: 100-240 VAC, 50-60Hz
- Power Consumption: 81W, 1.1A, PF: .63

Movement Range

• Pan: 630°/540°, Tilt: Infinite

Weight & Dimensions

- Width: 10.5 x 6.7 x 14.4 inches (265 x 170.5 x 366 mm)
- Weight: 9.3 lbs (4.2 kg)