

4-In-1 RGBW Mini Moving Head w/Zoom

Looking for a sharp new addition to your lighting rig? Then check out our Stiletto™ Z3 mini moving heads, they never get dull!

Stiletto™ Z3 fixtures are high in quality, yet totally affordable moving heads that come packed with 3* 15W ultra-bright 4-In-1 RGBW LEDs with awesome motorized liner zoom! Stiletto™ Z3's are ready to take a stab at becoming the new crowd favorite at your next show!

With fast pan/tilt motors, razor-sharp optics, ultra-smooth 16-bit dimming, and a narrow to wide 6.5°-60° zoomable beam angle, Stiletto™ Z3 fixtures are able to put on a high-energy lighting display of brightly colored moving beams in standalone, auto mode, sound active mode, or via 12/17-channel DMX modes.

Users can also access Stiletto™ Z3's settings by way of its 4-button LED control panel, which offers total control of every available feature including reversible pan/tilt, user-selectable fast or slow auto modes, sound active mode, mic sensitivity, individual RGBW color balance settings, motor reset, and factory reset.

On the back side of Stiletto™ Z3 fixtures you will find a single industry standard PowerCON® compatible input connector and 3-pin DMX In/Out jacks. Preparing the fixture for truss mounting is also a snap by attaching its included single underside clamp mounting bracket.

It is a super compact, lightweight, and quiet running mini moving head with a ton of spectacular features that you will love. And did I mention that it is flicker free? You bet it is!

And of course, the Stiletto™ Z3 is backed by Blizzard's 2-year warranty!

Photometric Data

Wide Beam:

Lux / Meter	All	Red	Green	Blue	White
1M	11,420	224	307	383	544
2M	308	70	91	116	148

Narrow Beam:

Lux / Meter	All	Red	Green	Blue	White
1M	21,990	4,860	5,790	7,760	10,330
2M	6,070	1,269	1,662	2,070	2,656
3M	2,756	609	748	956	956
4M	1,485	326	411	534	534
5M	973	222	262	343	343

Main Features

- 3* 15W ultra-bright 4-In-1 RGBW LEDs
- Pan: 540°/ Tilt: 270° (8-16 Bit Resolution)
- Motorized liner zoom
- 6.5°-60° beam angle
- Built-in auto and sound active programs
- Ultra-smooth 16-bit dimming system
- Internal fan cooling system
- Fast motors, quiet operation, and flicker free
- PowerCON® compatible power input connector
- Compact, high quality housing

STILETTO Z3™



Light Source

- 3* 15W ultra-bright 4-In-1 RGBW LEDs

Control

- Protocol: USITT DMX-512
- DMX Channels: 12/17-channels
- Standalone, Master/Slave, Auto, & Sound Active
- 3-pin DMX input/output
- Easy-to-use, 4-button LED control panel

Optical

- Beam Angle: 6.5°-60°

Power

- Operating Voltage: 100-260 VAC, 50-60Hz
- Fuse: 5A 250V
- Power Consumption: 65W, .82A, PF: .66

Operating Temperature

- Max. Operating Temp.: 104 degrees F (40 degrees C) ambient

Dimensions

- Width: 7.9 inches (21 cm)
- Depth: 5.5 inches (14 cm)
- Height: 11 inches (27 cm)
- Weight: 8.8 lbs (4 kg)

Warranty

- 2-year limited warranty, does not cover malfunction caused by damage to LEDs.