

Stiletto™ Z6

Want to add a ton of excitement to your next light show? You can't go wrong with the incredible fog cutting abilities of the ultra-sharp Stiletto™ Z6 moving head fixture with 6x multi-chip 4-in-1 RGBW 15W LEDs and an impressive 6.5°-60° zoomable beam angle.

Stiletto™ Z6 fixtures are affordable, high quality, and packed with goodies! They are very bright and can mix RGBW colors beautifully from a wide 60° throw, down to a tight 6.5° beam and everything in between. It has 4 user-selectable 32-bit dimming curve modes that are flicker-free and at your disposal directly from the control panel or via DMX for smoother (and slower) dimming capabilities! Then, the fast and precise user selectable 360°/540° pan and 270° tilt of the Stiletto™ Z6 make it a super aerial performer in a tiny, lightweight package!

This fixture also comes equipped with an easy-to-use 4-button LCD control panel, attractive housing (it's got all the right curves), industry standard powerCON® compatible power In/Out connections, 3-pin DMX In/Out jacks, and a single secure quarter-turn "Omega" quick connect type clamp bracket, making this one intensively engineered, incredible moving head effect fixture.

Stiletto™ Z6 LED fixtures are a brilliant addition to any light show with a ton of spectacular features that you and your audience will love!

Main Features

- 6* multi-chip 4-in-1 RGBW 15W LEDs
- 6.5°-60° degree zoomable beam angle
- 8/16-bit pan and tilt (360°/540° pan, 270° tilt)
- Four user selectable dimming curve modes via DMX
- Smooth 0-100% dimming, flicker free
- Built-in automated programs via master/slave
- Built-in sound activated programs
- USITT DMX-512 (15-channels)
- 3-pin DMX In/Out
- 4-button menu with LCD display
- PowerCon™ compatible AC power In/Out connectors

Warranty

- 2-year limited warranty, does not cover malfunction caused by damage to LEDs

STILETTO Z6™



Light Source:

- 6* multi-chip 4-in-1 RGBW 15W LEDs

Power:

- AC 100-240VAC, 50-60 Hertz
- Power Consumption 81W, 1.13A, PF: .61

Optical:

- 6.5°-60° degree zoomable beam angle

Luminous Intensity

- 14,404 Lux @ 2m (narrow), 2,410 Lux @ 5m (narrow), 588 Lux @ 2m (wide)

Thermal:

- 104 degrees F (40 degrees C) ambient

Control:

- USITT DMX-512
- DMX channels 15 channels
- Input: 3-pin XLR Male
- Output: 3-pin XLR Female
- Operating Modes: DMX512, Master/Slave, Auto, Sound Active, Standalone

Weight and Dimensions:

- Width: 9.5 in (24.1 cm)
- Depth: 7 in (17.8 cm)
- Height: 12 in (30.5 cm)
- Weight: 9.9 lbs (4.5 kg)