Go Getter Sound System

Technical Specifications



SIX YEAR WARRANTY

The Go Getter is perfect for voice projection in an indoor or outdoor setting, and for playing music during school activities. The unit delivers 109dB of intelligible speech, and is designed for users with little-to-no technical background.

Featuring a quick set-up and easy-to-use controls, the new Go Getter is a truly versatile sound system with true AC/DC operation, optional Bluetooth capability and improved battery life. The system is ideal for schools, corporate training, and places of worship.





(GG-8000CU2 Back Panel Shown)

Features

Reach Crowds of 500+

True AC/DC - 110/220V Power Supply

Single or Dual UHF Wireless with 16 User Selectable Channels

Optional CD/MP3 Combo Player

Comes with Standard Built-in Bluetooth

Remote Control for CD/MP3 Combo Player

LED Displays Charging and Low Battery

Two Microphone Combo Input Jacks

6.5" Woven Fiber Woofer & High-Output Horn Tweeter

Lightweight at just 20 Pounds

Improved "Limiter" Circuitry Reduces Distortion & Increases Intelligibility

Operates 6 - 8 Hours on a Single Charge

Speaker Out to Power Companion Speaker

GO GETTER MODELS

GG-8000	Go Get	ter with Bluetooth
GG-8000U		ter with Bluetooth reless receiver
GG-8000U		ter with Bluetooth reless receivers
GG-8000C		ter with Bluetooth MP3 combo player
GG-8000C	CD/MI	ter with Bluetooth, 23 combo player reless receiver
GG-8000C	CD/MI	ter with Bluetooth, 23 combo player reless receivers
GG-8001	Unpow	ered companion speaker

UHF WIRELESS

WH-8000 Wireless handheld microphone/ transmitter (540-570 MHz)

Wireless body-pack transmitter WB-8000 (540-570 MHz) (requires handsfree microphone) Microphone options

include:

Over-the-Ear/EM-TA4F, Lapel/LM-60, Collar/CM-60, Headband/HBM-TA4F

TECHNICAL SPECIFICATIONS

Rated Power Output Max SPL @ Rated Power 109dB @ 1 meter Frequency Response AC Power Regs. Dimensions (HWD) Weight (AC/DC)

75 watts AC/DC mode 60 Hz - 16 kHz 90 - 264 VAC, 50/60 Hz 18" x 11" x 9" (46 x 28 x 23 cm) 20 lbs/ 9.07 Kg

Inputs

Microphone (Two combo) Lo-Z (1 $K\Omega$), balanced, XLR

12 VDC condenser microphone

phantom power

Hi-Z (10 K Ω), balanced 1/4'' phone Hi-Z (10 K Ω), balanced 1/4'' phone

Auxiliary (line) Outputs

Line (post fader)

Lo-Z, buffered, 1/4"unbalanced/

balanced

Speaker Out 4-pole Neutrik Speakon® jack



(Features & Specifications Subject to Change Without Notice)

Anchor Audio, Inc.