# Simple Speaker Installation



**ICM6-730SET** 

## ALL-N-ONE CEILING SPEAKER

Includes Speaker, Transformer, Housing, Grill, and T-Bar Bracket

- Built-In Metal Housing
- 8 Ohms / 70 V / 100 V

Excellence in Audio Envirotainment



OWI, INC. tel: 310.515.1900 toll-free: 800.638.1694 fax: 310.515.1606 e-mail: info@owi-inc.com web: www.owi-inc.com





- Transformer, Housing and Grill.
- T-Bar Bracket



#### **GENERAL SPECIFICATIONS:**

MODEL NUMBER	6.5", 2-WAY Poly Coated Woofer w/ Swivel Tweeter		
Description:			
Impedance:	8 Ohms		
70 Volt Taps:	1.75W, 3.5W, 7W, 15W, 30W		
100 Volt Taps:	3.5W, 7W, 15W, 30W		
8 Ohms Taps:	60W		
Sensitivity (1W/1M):	86 dB		
Max Power:	120 W		
Nominal Power:	60 W		
Frequency Response:	55 Hz to 20 kHz		
Crossover:	4.2 kHz		
Input Connection:	Phoenix Connector		
Woofer Size:	6.5"		
Woofer Material:	Poly Coated Woofer		
Tweeter Size:	1"		
Tweeter Material:	PEI		
Grill Material:	Aluminum (Removable OWI Logo Sticker)		
Dimensions:	8"H x 10" Dia.		
Cut Out Size:	8 <sup>3</sup> /4"		
Mounting Hardware:	Kwik Klamps		
Mounting Bracket (Included):	T-Bar Bracket		
Paintable:	Yes		
Outdoor Rated:	No		
(Covered):	(Yes)		

#### **RECOMMENDED ACCESSORIES:**

#### **Volume Control**

Model 25WPVC (25W) Model 72WPVC (72W)

### **Attenuators**

Model OWI1070MW (70W) Model OWI2570SW (25W)



OWI, INC.

17141 Kingsview Avenue, Carson, CA 90746 USA

tel: 310.515.1900 toll-free: 800.638.1694 fax: 310.515.1606 e-mall: Info@owl-Inc.com web: www.owl-Inc.com