

Prolink 500 wireless intercom system

MADE IN THE USA









- Heavy Duty 4-Pin XLR Connector
- Choice of Single or Dual Muff Headsets
- A/B Channel Selection
- "Push to Talk" or "Always On" Modes
- Microphone Gain Setting
- Out of Range Indicator LED
- Transmits up to 500' Line of Sight
- Rechargeable Batteries Included
- Gang Charger for Four Belt Packs
- FCC License Free

MADE IN USA





The ProLink 500 is a digital wireless intercom system that

allows full duplex communication between

four users simultaneously with the option of unlimited number of listen only belt packs. The transmitter and receiver operate utilizing the FCC license free 902 - 928 MHz range for the U.S. without the need for a base station.

The ProLink 500 has the capability to transmit

up to 500 feet line of sight and allows communication through walls

and glass. Depending on usage, it can operate up to 12 hours using rechargeable alkaline batteries. Each belt pack will be able to communicate in "Push-to-Talk" mode, which always receives but only transmits when the PTT button is pushed, or "Always On" mode which provides completely hands-free communication.

Features

Heavy Duty 4-Pin XLR Connector Choice of Single, Dual Muff or Lightweight Headsets A/B Channel Selection "Push to Talk" or "Always On" Modes Microphone Gain Setting **Out of Range Indicator LED** Low Battery Indicator LED Charging Indicator LED Rechargeable Batteries Included Gang Charger for Four Belt Packs FCC License Free


500 ft. Line of Sight Wireless Communication

Components

П

-
Master belt pack
Remote belt pack
Listen only belt pack
Dual ear muff headset
Single ear muff headset
Dual muff headset listen only
Single muff headset listen only
Lightweight headset
Gang charger
Anchor Armor hard case -

Prolink 500



Packages

PRO-540 Four User Package:

One BP-500M master belt pack, three BP-500R remote belt packs, four headsets (H-2000 or H-2000S), one GC-500 gang charger & one lightweight, high-density cardboard case

PRO-570 Seven User Package:

Two BP-500M master belt packs, Five BP-500R remote belt packs, Seven headsets (H-2000 or H-2000S), Two GC-500 gang charger & one lightweight, high-density cardboard case

Technical Specifications

ProLink Belt Pack (BP-500)

RF Frequency Range 902-928MHz Modulation FSK Range (line of sight) Duplex 500' / 152.4 m Antenna 1/2 - wavelenath dipole **Power Supply** 9VDC, 1.2ADC **Battery Life** 12 hours Weight 15 oz / 0.42kg (with batteries) **Dimensions** 4.5" x 6.25" x 3.75" (114.3 x 158.75 x 95.25 mm)

Single-Ear (H-20005) & Dual-Ear Headphones (H-2000)

Drivers Dynamic, 40mm **Impedance** 300 Ω +/- 15% 20Hz - 20kHz Frequency Response SPL 91dB +/- 3dB Rated Power > 40mW Distortion

Microphone Dynamic, Uni-directional, Low impedance

Microphone Sensitivity

Referenced to OdB=1V/ µbar,1kHz Min -85 dB / Typical -83 dB /

Max -81 dB

Frequency Response 200Hz-12kHz Connector Plug 4-pin XLR, female Single: 13 oz / 0.37 kg & Weight Dual: 16 oz / 0.45 kg

Bluetooth Range

10-20 ft LOS Frequency 2.4 GHz

(Features & Specifications Subject to Change Without Notice)



Anchor Audio, Inc.